



DW-36 Thinner

Features:

1. High quality thinner, specially developed for DW primer, basecoat and topcoat
2. Available with fast, standard, slow and extra slow drying speed to match different products and different application requirements.

Usage: To reduce the application viscosity, increase the smoothness of paint film
Good solubility.

Characteristic:



DW-36 Fast	1K basecoat only, with very fast evaporation speed, suitable for spot repair or application below 15°C.
DW-36 Normal	Standard thinner for 1K basecoat and 2K products, with medium evaporation speed, suitable for spot repair or application at 15~25°C.
DW-36 Slow	For 1K basecoat and 2K products, with slow evaporation speed, suitable for spot repair or overall refinishing or application at 25~30°C.
DW-36 Extra Slow	2K products only, with very slow evaporation speed, suitable for overall refinishing, large area application or application over 30°C.

Note:

1. If the temperature and humidity are too high, 10~30% DW707 Retarder Solvent can be added.
2. Shelf life: 2 years in original sealed can at cool and dry place at 25°C. Packaging: 1L, 4L or 5L.





DW-702 Fade Out Thinner

Features: To dissolve the rough overspray area of new and existing finishes and achieve an invisible transition for panel repair.

Substrate: overspray area of 2k solid colors, clearcoat in panel repair.



	<p>Mixing Ratio: The product is ready for use. Can mix with the paint remained in the spray gun in the ratio of 1: 1</p>
	<p>Application Method: Spray lightly one coat over the overspray area with DW-702 right after the finish. Second coat in 20 seconds.</p>

Note:

1. Not suitable for 1K basecoat and primer .
2. Shelf life: 2 years in original sealed can at cool and dry place at 25°C. Packaging:1L