



## WB-2K Series Hardener

### Features:

1. Specially designed for WB-2K topcoat and clearcoat.
2. A series of yellow resistant hardener for auto paint.
3. To match different products,application area and conditions.
4. It includes various versions as standard,fast,slow drying and high solid hardener and so on.

### Match with:

WB-2K solid coat ,WB-800 standard clear coat and WB-860 high solid clear coat.

### Characteristic:

WB-810 Fast Hardener	Medium solid fast drying hardener for topcoat, suitable for spot repair and low temperature application below 18°C
WB-810 Standard Hardener	Medium solid standard drying hardener for topcoat, suitable for spot repair overall refinish at 18°C-30°C
WB-810 Slow Hardener	Medium solid slow drying hardener for topcoat, suitable for spot repair overall refinish above 30°C
WB-860 High solid Fast Hardener	High solid fast drying hardener for WB-860 High solid clear coat, suitable for spot repair and low temperature application below 18°C
WB-860 High solid Standard Hardener	High solid standard drying hardener for WB-860 High solid clear coat, suitable for spot repair overall refinish at 18°C-30°C
WB-860 High solid Slow Hardener	High solid slow drying hardener for suitable for WB-860 High solid clear coat, suitable for spot repair overall refinish above 30°C

### Note:

1. Choose right hardener according to temperature, humidity and drying condition, generally, better to use fast drying hardener below 18°C, standard hardener at 18~30°C and slow drying hardener above 30°C.
2. Please seal the can tightly after use as hardener is sensitive to moisture. Absorption of moisture can lead to chemical reaction and concreting. Please keep away from direct sunlight in storage.
3. Shelf life:2 years in original sealed can at cool and dry place at 25°C. Packaging:0.5L, 1L or 2.5L